Survitec

UNIVERSAL LIGHT

LIFEJACKET LIGHT



The universal light is one of the only lights available to date that can accommodate both surface and recess mounting solutions effectively. The light can be attached to a point on the jacket to become a surface light or placed into a circular housing unit which is permanently recessed in the lifejacket.

When recess mounts are used the light has an extremely low profile and is non-intrusive. Once expired the light is easily replaced. If purchasing the recessed mounting option the light is supplied with two brackets allowing swap-out of both Crewsaver and non-Crewsaver light options.

Additionally, the light can be purchased with either an attached cable and water activated sensor or without cable and integrated sensor. The integrated sensor option will flash automatically once fully immersed in water where as the cable with sensor option will flash only on constant contact with water.

FEATURES

- ACTIVATES ON CONTACT WITH WATER OR MANUALLY
- FLASHING LED LIGHT
- SOLAS, MED AND USCG APPROVED
- MINIMUM 8 HOURS LIGHT DURATION
- MAXIMUM 5 YEAR STORAGE LIFE



11

This flashing light meets all relevant safety standards to keep you visible in the worst of scenarios

UNIVERSAL LIGHT

LIFEJACKET LIGHT

LIGHT OPTIONS

Integrated sensor






SURFACE BRACKET





Integrated Sensor







51g


CIRCULAR RECESS


With Cable



Integrated Sensor







UNIVERSAL LIGHT

LIFEJACKET LIGHT

CIRCULAR RECESS ADAPTERS



Recess



For Universal light housing

Raised



For use with non-Crewsaver light housings

LIFEJACKET LIGHT DISPOSAL

Disposing of used and expired lights should be in accordance with local regulations. This should be done through an approved environmental disposal agent and not disposed with other household or commercial waste.

SWITCHING

IMO regulations state that a flashing lifejacket light has to have the option to be switched off. All Crewsaver lights can be turned on and off easily at the touch of a button.

OPERATION

All Universal lights activate automatically when the switch is fully immersed in water and will switch off if removed. Universal lights with integrated sensor activate automatically when fully immersed in water and will remain activated until manually switched off.

All Crewsaver Premier Foam lifejackets are available with any Crewsaver light option and can be supplied as standard.

UNIVERSAL LIGHT

LIFEJACKET LIGHT

TECHNICAL DATA		
Light Output Vertical/Horizontal	Min 0.75 cd Max 6.0 cd	
Light Output Surface Mount	8.0 cd	
Light Duration	Min 8 hour	
Light Type	Flashing LED	
Material	PCTG/ABS/Silicone	
Storage Temperature	-30 °C to +65 °C	
Operating Temperature	-1 °C to +30 °C	
Storage Life	5 Years	
Activation	Water or Manual	
Battery Type	Lithium Manganese Dioxide	
Weight	49.4 g (Light Only)	

Ordering Information

PRODUCTS		
Product Number	Product Name	
10281	Universal Light Solas and Surface Mount Bracket	
10282	Universal Light Solas and Circular Recessed Adaptors	
10276	Universal Light Solas with Recessed Mount Bracket and Integrated Sensor	
10278	Universal Light Solas with Surface Mount Bracket and Integrated Sensor	

Spares

PRODUCTS		
	Product Number	Product Name
	10269	Universal Circular Recessed Housing

APPROVALS
SOLAS/MED and USCG





