



CREWSAVER SURFACE LIGHT (CSL)

LIFEJACKET LIGHT ↓

Approved to IMO, SOLAS, MED, MCA and RORC requirements, this flashing light meets all relevant safety standards to keep you visible in the worst of scenarios. The Crewsaver Surface Light is suitable for all types of lifejackets by using the provided CSL fitting kit.

FEATURES

- FLASHING FOR OPTIMUM VISIBILITY AT SEA
- POWERED BY A DURACELL ULTRA 3V LITHIUM-ION BATTERY
- HIGH POWERED WHITE LED LIFEJACKET LIGHT
- MINIMUM LIGHT INTENSITY 1.3CD AT 0° (REQ. 075CD)
- OPTIMUM OUTPUT LEVELS EXCEEDS 6CD
- BURN TIME INCREASED TO 60 HOURS



This flashing light meets all relevant safety standards to keep you visible in the worst of scenarios

CSL

CREWSAVER SURFACE LIGHT



Ordering Information

PRODUCTS	
Product Number	Product Name
10220	Crewsaver Surface Light Packaged
10226	Crewsaver Surface Light Un-packaged

TECHNICAL DATA

Light Output:	1.3 Cd Min
Duration:	60 hours
Material	PCTG/ABS
Type	Flashing LED
Battery Type	Lithium Manganese Dioxide
Storage Life	5 years
Storage Temperature	-30 °C to +65 °C
Operating Temperature	-1 °C to +30 °C
Activation	Water or Manual
Dimensions (L) X (W) X (H)	45 x 31 x 39 mm

APPROVALS

Approved to IMO, SOLAS, MED, MCA and RORC requirements



survitec

GET IN TOUCH

Phone +44 (0) 1329 820 000

Email crewsaver.sales@survitecgroup.com

www.survitecgroup.com

Survitec House, Lederle Lane, Gosport, PO13 0FZ